REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2020/01/20	Vicky	Initial Released



C1



C2

AB-BD XX FL-BDBR-QE XXX

03: 3Pin

XXX: 0.5~99Meters
A05: 0.5 Meter
001: 01 Meter
002: 02 Meters
:
099: 99 Meters





Pin Out	3 White 白 2 Green 綠 1 Black 黑 Pin # Wire
C2	 3P
C1	 3P

Pin Assignments Front View

Note:
* QC Important Dimension
* Waterproof Rate: IP68, Mated
  IP68: 1M depth of water in 24hours
* Connector: Thermoplastic, Black
* Pin: Copper Alloy, Gold Plated
* Cable: SJTW, 18#*3C, PVC Jacket, Black, OD8.0mm
* Cable Length Tolerance: 0.5M: +60/-0mm
  01M: +60/-0mm
  02~03M: +120/-0mm
  04~05M: +160/-0mm
  06~10M: ±100mm
  11~20M: ±200mm
  21~30M: ±300mm
  31~99M: ±500mm

UNIT: mm

TOLERANCE ±0.5mm

TITLE: ACC, XLOK, B-5A, DB-ENDED FF

SCALE 1:2 | SIZE A4 | SHEET 1 OF 1

REV. A | WC-REV. A.5 | QC: Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
	Vicky	2020-01-20
DWG NO: AB-BDXXFL-BDBR-QEXXX	CHECKED BY: Rita	DATE: 2020-01-20
CUSTOMER: ALTW	APPROVED BY: Max	DATE: 2020-01-20

W10814-03-[redacted]01A2

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.