


THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2020/01/03	Ruru	Initial Released



- Note:
- \*  $\varnothing$  Important Dimension.
  - \* Waterproof Rate: IP68, Mated.  
IP68: 1M depth of water in 24 hours.
  - \* Connector: Thermoplastic, Black
  - \* Pin: Copper Alloy, Gold Plated.
  - \* Cable: UL21388, PVC Jacket, Black.
  - \* Cable Length Tolerance: 0.5M: +60/-0mm  
01M: +60/-0mm  
02~03M: +120/-0mm  
04~05M: +160/-0mm  
06~10M: ±100mm  
11~20M: ±200mm  
21~30M: ±300mm  
31~99M: ±500mm


UNIT: mm		TITLE	ACC, XLOK, C-10A, DB-ENDED MM	
TOLERANCE	±0.5 mm	SCALE	1:2	SIZE A4
		REV.	A	WC-REV.
				$\varnothing$ : Inspection item

**Amphenol LTW**  
安費諾亮泰企業股份有限公司

ITEM NO.	DRAWN BY	DATE
	Ruru	2020-01-03
DWG NO.	CHECKED BY	DATE
AB-CBXXML-CBHL-QDXXX	Rita	2020-01-03
CUSTOMER	APPROVED BY	DATE
ALTW	Max	2020-01-03

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

5P	PVC	7.6	16	AB-CB05ML-CBHL-QDXXX
4P		6.8		AB-CB04ML-CBHL-QDXXX
Contacts	Cable Jacket	Cable OD	AWG	Item No.



AB- CB XX M L - CB H L - Q D XXX

04: 4Pin  
05: 5Pin

XXX: 0.5~99Meters  
A05: 0.5 Meter  
001: 01 Meter  
002: 02 Meters  
:  
099: 99 Meters

UNIT:mm

TOLERANCE ± 0.5 mm

TITLE ACC, XLOK, C-10A, DB-ENDED MM

SCALE 1:2 SIZE A4 SHEET 2 OF 2

REV. A WC-REV. Inspection item

**Amphenol LTW**  
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY Ruru	DATE 2020-01-03
DWG NO AB-CBXXML-CBHL-QDXXX	CHECKED BY Rita	DATE 2020-01-03
CUSTOMER ALTW	APPROVED BY Max	DATE 2020-01-03