



THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2020/01/17	Ruru	Initial Released



- Note:
- * \varnothing Important Dimension.
 - * Waterproof Rate: IP68, Mated.
IP68: 1M depth of water in 24 hours.
 - * Connector: Thermoplastic, Black.
 - * Pin: Copper Alloy, Gold Plated.
 - * Cable: UL21996, (26#*4P+D+AL)+12#*3C+AL, PVC Jacket, Black, OD13.5
 - * Cable Length Tolerance: 0.5M: +60/-0mm
01M: +60/-0mm
02~03M: +120/-0mm
04~05M: +160/-0mm
06~10M: ±100mm
11~20M: ±200mm
21~30M: ±300mm
31~99M: ±500mm

UNIT:mm		
TOLERANCE	±0.5 mm	

TITLE ACC, XLOK, D-20A+5A, DB-ENDED FF		
SCALE 1:2	SIZE A4	SHEET 1 OF 2
REV. A	WC-REV.	\varnothing : Inspection item


Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY Ruru	DATE 2020-01-17
DWG NO AB-DCDXXFL-DCDFL-QFXXX	CHECKED BY Rita	DATE 2020-01-17
CUSTOMER ALTW	APPROVED BY Max	DATE 2020-01-17

AB- DCD XX F L - DCD F L - Q F XXX

12: 12Pin

XXX: 0.5~99Meters
 A05: 0.5 Meter
 001: 01 Meter
 002: 02 Meters
 :
 099: 99 Meters



C1 & C2
Pin Assignments
Front View

12	Drain (26AWG)	地線	
11	Gray (26AWG)	灰	Twist 對線
10	Yellow (26AWG)	黃	
9	Orange (26AWG)	橘	Twist 對線
8	Violet (26AWG)	紫	
7	Blue (26AWG)	藍	Twist 對線
6	Red (26AWG)	紅	
5	Green (26AWG)	綠	Twist 對線
4	White (26AWG)	白	
3	Black (12AWG)	黑	
2	White (12AWG)	白	
1	Green (12AWG)	綠	
Conn.	Wire Color		
Pin Out			

UNIT:mm		
TOLERANCE		
± 0.5 mm		

TITLE ACC, XLOK, D-20A+5A, DB-ENDED FF			
SCALE 1:2	SIZE A4	SHEET 2 OF 2	
REV. A	WC-REV.	QC: Inspection item	

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY Ruru	DATE 2020-01-17
DWG NO AB-DCDXXFL-DCDFL-QFXXX	CHECKED BY Rita	DATE 2020-01-17
CUSTOMER ALTW	APPROVED BY Max	DATE 2020-01-17