




REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	FN-8B0148~151	2008/09/25	Shin	Add Note
C	FN1630270~273	2016/03/07	Ruru	Change Logo & Note




Cable ② CD-14PMMM-SL7000 ①
Color: Black

CD-14PMMM-SL7AXX
 XX:01~99Meter
 01:01Meter
 02:02Meters
 :
 :
 99:99Meters
 Cable Length(L):01~99Meters



Recommended Panel Cut-Out



Pin Assignments Front View

7	Pink	粉紅	14	Brown/White	棕/白
6	Gray	灰	13	Black /White	黑/白
5	Yellow	黃	12	Light Green	淺綠
4	Green	綠	11	Purple	紫
3	White	白	10	Orange	橘
2	Blue	藍	9	Black	黑
1	Brown	棕	8	Red	紅
Conn.	Wire Color		Conn.	Wire Color	

Pin Out

- Note:
- * @ Important Dimensions To Check.
 - * Waterproof Rate: IP67
 - * Housing: Nylon+GF,Black
 - * Male Pin: Copper Alloy,Gold Plated
 - * Cable: UL2464 24AWG*14C+D+AL/My Black,PVC Jacket UV Resistant, OD=7.0
 - △* Use with waterproof cap or dust cap
Panel Thickness Max: 1.2mm
 - △* Use without waterproof cap or dust cap
Panel Thickness Max: 2.0mm
 - △* Cable Length Tolerance: 01M: ±40mm
02M~05M: ±60mm
06M~10M: ±100mm
11M~30M: ±200mm
31M~99M: ±500mm

UNIT:mm		TITLE	Middle, Cable Screw 14Pin M Conn M Pin		ITEM NO	DRAWN BY	DATE
TOLERANCE	±0.5 mm	SCALE	Free	SHEET 1 OF 1	DWG NO	CHECKED BY	DATE
		REV.	C	SIZE A4	CUSTOMER	APPROVED BY	DATE
				@ :Inspection Item	ALTW	Lisa	2016/03/07

Amphenol LTW
安費諾亮泰企業股份有限公司

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.