


REV.	ECN NO.	DATE	SIGN	DESCRIPTION
C	LEN1660267~270	2016/05/31	Vicky	Update Logo
D	C210219	2021/03/17	Vicky	△ X4
E	C210796	2021/05/24	Vicky	△ X1



Pin Out	5	Green	綠
	4	Black	黑
	3	Blue	藍
	2	White	白
	1	Brown	棕
	Pin #	Wire	
Conn.			
	5P		
Pin Assignments Front View			

△ 12-XXBFIM-SL8BXX
 XX: No. Of Pin
 XX: 01~99Meters
 01: 01Meter
 02: 02Meters
 :
 :
 99: 99Meters
 Cable Length(L): 01~99Meters

- △ Note:
- * RoHS Compliant
 - * △ Important dimension
 - * Waterproof rate: IPX8, mated 1m/24h
 - * Connector
 Housing: Thermoplastic, Black
 Pin: Copper alloy, Gold plated
 O-Ring: Rubber, Green
 Nut: Metal
 Outer mold: Thermoplastic, Black
 - * Cable: 22#*5C+Insulation, OD=5.0mm, PU Jacket, Black
 - △ * Cable length tolerance:
 1M: +50/-0 mm
 1M < L ≤ 3M: +100/-0 mm
 3M < L ≤ 5M: +150/-0 mm
 5M < L ≤ 10M: ±100 mm
 10M < L ≤ 20M: ±200 mm
 20M < L ≤ 30M: ±300 mm
 △ 30M < L ≤ 99M: ±500 mm

UNIT:mm	TITLE	
TOLERANCE	O SEN, M12 A (I) △△	
±0.5mm	CABLE W/O SR, F, I, MOLDING	
SCALE	SHEET	OF
Free	1	1
REV.	SIZE	◎: Inspection Item
E	A4	

Amphenol LTW
 安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
DWG. NO	CHECKED BY	DATE
CUSTOMER	APPROVED BY	DATE
12-XXBFIM-SL8BXX	Vicky	2016/05/31
ALTW	Rita	2016/05/31
	Lisa	2016/05/31

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.