



REV.	ECN NO.	DATE	SIGN	DESCRIPTION
D	LEN1660504~507	2016/06/06	Vicky	Update Logo
E	C210219	2021/03/15	Vicky	△X4
F	C210796	2021/05/24	Vicky	△X4



Pin Out	Pin #	Wire
5	Green	綠
4	Black	黑
3	Blue	藍
2	White	白
1	Brown	棕



Pin Assignments
Front View

△12P-XXBMIM-SL8AXX
 XX: No. Of Pin
 XX: 01~99Meters
 01: 01Meter
 02: 02Meters
 :
 :
 99: 99Meters
 Cable Length(L): 01~99Meters

- △ Note:
- * RoHS Compliant
 - * @ Important dimension
 - * Waterproof rate: IPX8, mated 1m/24h
 - * Connector
 - Housing: Thermoplastic, Black
 - Pin: Copper alloy, Gold plated
 - Nut: Thermoplastic, Black
 - Outer mold: Thermoplastic, Black
 - * Cable: UL2464, 22#*5C+Talcum, OD=5.5mm, PVC Jacket, UV Resistant, Black
 - △ * Cable length tolerance:
- 1M: +50/-0 mm
 1M < L ≤ 3M: +100/-0 mm
 3M < L ≤ 5M: +150/-0 mm
 5M < L ≤ 10M: ±100 mm
 10M < L ≤ 20M: ±200 mm
 20M < L ≤ 30M: ±300 mm
 △ 30M < L ≤ 99M: ±500 mm

UNIT:mm		TITLE
TOLERANCE	±0.5mm	0 SEN, M12 A -PLASTIC(I) △△ CABLE W/O SR, M, I, MOLDING
SCALE	Free	SHEET 1 OF 1
REV.	F	SIZE A4
		@ : Inspection Item

Amphenol LTW
 安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
DWG NO	CHECKED BY	DATE
CUSTOMER	APPROVED BY	DATE
ALTW	Lisa	2016/06/06

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.