






REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN1570029	2015/05/12	Ruru	Change Logo



Recommended Panel
Cut-Out



- Notes:
- * Waterproof Rate: IP68
 - * Screw Nut: Nylon, Gray
 - * Clamp Ring: Nylon, Gray
 - * Sealing Nut: Nylon, Gray
 - * Gasket: EPDM, Black
 - * Seals: EPDM, Black
 - * Panel Thickness: 7.5mm max.
 - * Cable Range: $\varnothing 6\text{mm} \sim \varnothing 10\text{mm}$
 - * Spanner Size:
 - ① Screw Nut: 22mm
 - ③ Body: 22mm
 - ⑤ Sealing Nut: 22~22.9mm

UNIT:mm		TITLE PG 9 Straight with SR		ITEM NO CSG-09G004		DRAWN BY Ruru		DATE 2015-05-12	
TOLERANCE .X ±0.25 .XX ±0.1 .XXX ±0.05 ANGLES ±1°		SCALE 1:1	SIZE A4	SHEET 1	DWG NO CSG-09G004	CHECKED BY Rita		DATE 2015-05-12	
REV. B		WC-REV. A.1	QC: Inspection item		CUSTOMER ALTW	APPROVED BY Lion		DATE 2015-05-12	

Amphenol LTW
安費諾亮泰企業股份有限公司

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.